

GORDON AMPLIFICATORE AMP05K2



FEATURES

- WITH SHORT CIRCUIT, OVERCURRENT PROTECTIONS AND OVERHEAT PROTECTION
- NO IMPACT NOISE WHEN TURNING ON AND OFF THE DEVICE
- INTELLIGENT TEMPERATURE CONTROL FAN AIDS COOLING AND REDUCING NOISE
- THREE KIND OF OUTPUT: MONO, STEREO AND BRIDGE
- SIGNAL, CLIP, PROTECT FAN, POWER INDICATION
- INPUT: XLR, 1/4" JACK, RCA
- OUTPUT: SPEAKON NL4, BINDING POSTS
- POWER SUPPLY: AC115/60Hz AND AC230V/50Hz VOLTAGE SELECT

CLASSIFICATION	AB
OUTPUT POWER 4 OHM	2x250 W
OUTPUT POWER 8 OHM	2x200 W
BRIDGE @ 4 OHM	500 W
XLR, 1/4" JACK INPUT	0.7mv
RCA INPUT	0.35mv
S/N	≥ 96dB
FREQ. RESPONSE	15Hz - 25 KHz
THD 1KHz	≤ 0.5%
INPUT RESISTANCE	10KΩ UNBALANCED, 20K BALANCED
POWER SUPPLY	AC115/60 AC230V/50Hz